


75W DALI LED Driver (Constant Voltage)



Features


- UL certification
- ENEC certification
- Universal input 100-277 VAC
- Class II power supply
- Compatible with universal DALI masters that support DT6
- 4 DALI addresses can be manually assigned via buttons and showed on digital display or automatically assigned by DALI masters
- Can be used to control constant voltage single colour, tuneable white, RGB/RGBW LED lighting
- IP20 rating

Safety

- The product should be installed and serviced by a qualified person
- Please avoid exposure to sun and rain
- Always be sure to mount this unit in an area with proper ventilation to avoid overheating

- Please check if the output voltage of any LED power supplies used comply with the working voltage of the product
- Make all the connections before you plug in the main power supply.

Physical Dimensions



Ordering Information

Part Number	Description
72306	75W Constant Voltage DALI Driver



Specifications

Item	Specification
Input Voltage	100 to 277 V AC
Input Frequency	50/60 Hz
Maximum Total Output Power	75 W
Total number of Channels	4
Maximum Output Voltage	24 V
Maximum Output Current	3.12 A CH1 + CH2 + CH3 + CH4 = 3.12A
Dimming Interface	DALI/ Push Dim

Item	Specification	
Dimming Method	Pulse Width Modulation	
Device Protection	Short Circuit	Recovers automatically after fault condition is removed
	Over current	
	Over Temperature	
Operating Temperature	-20 °C to 45 °C	
Working Humidity	10% to 95% non-condensing	
IP Rating	IP20	

Due to continuous improvements and innovations of all ENTTEC products, specifications and features are subject to change without notice.

Wiring Diagrams



enttec.com

MELBOURNE AUS / LONDON UK / RALEIGH-DURHAM USA